

# CEILING RECESSED

**Art Number** WI 111016

Model 10W

























# Features

SHEEN series adopts high lumen SMD LED, PMMA diffuser with even light output which boosts its complete size and functions, such as wall switch, slide switch, Wifi, 2.4G, emergency and sensor.


Body made with aluminum die cast and plastic-PC reflector gives good output Aluminum die cast heat sink resist the heat dissipation

Lifespan is up to 50,000 hrs

Available with remote driver and dimmable with Triac, 0-100V & DALI

Easy to install, use stainless steel spring, safe and durable

Available other CCT on Request



#### **Product Specification**

LED Chip SMD LED 10W Power

Input 100-240VAC with remote driver Output 685lm(3K)/700lm(4K)/720lm(5K)

CCT 2700K(27)/3000K(30)/4000K(40)/5000K(50)

Power Factor >0.9

### Technical Data

IP Rating IP44


Housing Die cast aluminum Heat sink Die cast aluminum Finishing White (02)/Black(04)

Reflector Plastic+PC Diffuser РММА

HO5RN-F 2x0.75 mm<sup>2</sup>/ L=0.5m (low voltage) Power Cable

Mounting Sleeve Stainless steel Cutout Ø70mm Weight 0.24Kg CTN/PCS 50pcs

### Photometric Light Distribution



#### Photometric Data

CRI +08 Luminous Eficacy 68.5lm/W 90°(90) Beam Angle Operating Temp. -20°C~+45°

Order Code Example Artnumber

WL111016

Finish WH(02) Beam Angle 90°(90)

Color Temp 3000K(30)

WL111016.02.90.27