SHEEN


Art Number WI 111017

Model 1.3W



38 Ø110

Photometric Light Distribution



CEILING RECESSED 13V



Features

SHEEN series adopts high lumen SMD LED, PMMA diffuser with even light output which boosts its complete size and functions, such as wall switch, slide switch, Wifi, 2.4G, emergency and sensor. Body made with aluminum die cast and plastic-PC reflector gives good output Aluminum die cast heat sink resist the heat dissipation Lifespan is up to 50,000 hrs

Available with remote driver and dimmable with Triac, 0-100V & DALI Easy to install, use stainless steel spring, safe and durable Available other CCT on Request

Product Specification

| LED Chip | SMD LED |
|--------------|---|
| Power | 13W |
| Input | 100-240VAC with remote driver |
| Output | 850lm(3K)/880lm(4K)/900lm(5K) |
| CCT | 2700K (27) / 3000K (30) / 4000K (40) / 5000K (50) |
| Power Factor | >0.9 |

Technical Data

| IP Rating | IP44 | |
|-----------------|--|--|
| Housing | Die cast aluminum | |
| Heat sink | Die cast aluminum | |
| Finishing | White (02)/ Black(04) | |
| Reflector | Plastic+PC | |
| Diffuser | PMMA | |
| Power Cable | H05RN-F 2x0.75 mm²/ L=0.5m (low voltage) | |
| Mounting Sleeve | Stainless steel | |
| Cutout | Ø90mm | |
| Weight | 0.4Kg | |
| CTN/PCS | 24pcs | |
| | | |

Photometric Data

| CRI | 80+ |
|------------------|-----------------|
| Luminous Eficacy | 65.4lm/W |
| Beam Angle | 90° (90) |
| Operating Temp. | -20°C~+45° |

| Order Code | e Example | | | | |
|-----------------------|-----------------------------|--------------------------------|-------------------------|--|--|
| Artnumber WL111016 | Finish ^{WH(02)} | Beam Angle 90°(90) | Color Temp 3000K(30) | | |
| WL111016.02.90.27 | | | | | |



www.wilmarintl.com