

# CEILING RECESSEI

**Art Number** WI 111018

Model 18W

























## Features

SHEEN series adopts high lumen SMD LED, PMMA diffuser with even light output which boosts its complete size and functions, such as wall switch, slide switch, wifi, 2.4G, emergency and sensor.

Body made with aluminum die cast and plastic-PC reflector gives good output Aluminum die cast heat sink resist the heat dissipation

Lifespan is up to 50,000 hrs

Available with remote driver and dimmable with Triac, 0-100V & DALI

Easy to install, use stainless steel spring, safe and durable

Avilable other CCT on Request

## **Product Specification**


LED Chip SMD LED 18W Power

Input 100-240VAC Remote driver

Output 1320lm(3K)/1360lm(4K)/1420lm(5K)

CCT 2700K(27)/3000K(30)/4000K(40)/5000K(50)

Power Factor >0.9



30

### Technical Data

IP Rating IP44

Housing Die cast aluminum Heat sink Die cast aluminum Finishing White (02)/Black(04)

Reflector Plastic+PC Diffuser РММА

HO5RN-F 2x0.75 mm<sup>2</sup>/ L=0.5m (low voltage) Power Cable

Mounting Sleeve Stainless steel Cutout Ø120mm Weight 0.59Kg CTN/PCS 30pcs

## Photometric Light Distribution

UNIT: cd C0/180, 93 deg C30/210, 93.1 deg C60/240, 93.0 deg C90/270, 93.0 deg 18W 3000K 90°

#### Photometric Data

CRI +08 Luminous Eficacy 73lm/W 90°(90) Beam Angle Operating Temp. -20°C~+50°

Order Code Example Artnumber Finish Beam Angle Color Temp WL111018 WH(02) 90°(90) 3000K(30) WL111018.02.90.27

