

CEILING RECESSED

Art Number WI 111019

Model 25W























Features

SHEEN series adopts high lumen SMD LED, PMMA diffuser with even light output which boosts its complete size and functions, such as wall switch, slide switch, wifi, 2.4G, emergency and sensor.


Body made with aluminum die cast and plastic-PC reflector gives good output Aluminum die cast heat sink resist the heat dissipation

Lifespan is up to 50,000 hrs

Available with remote driver and dimmable with Triac, 0-100V & DALI

Easy to install, use stainless steel spring, safe and durable

Avilable other CCT on Request



Product Specification

LED Chip SMD LED 25W Power

Input 100-240VAC with remote driver Output 1850lm(3K)/1900lm(4K)/2000lm(5K)

CCT 2700K(27)/3000K(30)/4000K(40)/5000K(50)

Power Factor >0.9

Photometric Light Distribution

30

UNIT: cd - C0/180, 95.1 deg - C30/210, 95.1 deg - C60/240, 95.2 deg - C90/270, 95.2 deg 25W 3000K 90° зфо 900 -6l

-30

Technical Data

IP Rating IP44

Housing Die cast aluminum Die cast aluminum Heat sink Finishing White (02)/Black(04)

Reflector Plastic+PC

Power Cable $HO5RN-F 2x0.75 \text{ mm}^2/L=0.5m \text{ (low voltage)}$

Mounting Sleeve Stainless steel Cutout Ø140mm Weight 0.70Kg CTN/PCS 30pcs

Photometric Data

+08 Luminous Eficacy 74lm/W 90°(90) Beam Angle Operating Temp. -20°C~+50°

Order Code Example Artnumber Finish Beam Angle Color Temp WL111018 WH(02) 90°(90) 3000K(30) WL111018.02.90.27