

CEILING RECESSEI

Art Number WI 111020

Model 35W

RoHs (E F























Features

SHEEN series adopts high lumen SMD LED, PMMA diffuser with even light output which boosts its complete size and functions, such as wall switch, slide switch, wifi, 2.4G, emergency and sensor.


Body made with aluminum die cast and plastic-PC reflector gives good output Aluminum die cast heat sink resist the heat dissipation

Lifespan is up to 50,000 hrs

Available with remote driver and dimmable with Triac, 0-100V & DALI

Easy to install, use stainless steel spring, safe and durable

Avilable other CCT on Request



Product Specification

LED Chip SMD LED 35W Power


Input 100-240VAC with remote driver

Output 2600lm(3K)/2680lm(4K)/2760lm(5K)

CCT 2700K(27)/3000K(30)/4000K(40)/5000K(50)

Power Factor >0.9

Photometric Light Distribution



Technical Data

IP Rating IP44

Housing Die cast aluminum Heat sink Die cast aluminum Finishing White (02)/Black(04)

Reflector Plastic+PC Diffuser РММА

HO5RN-F 2x0.75 mm²/ L=0.5m (low voltage) Power Cable

Mounting Sleeve Stainless steel Cutout Ø160mm Weight 0.825Kg CTN/PCS 20pcs

Photometric Data

CRI +08 Luminous Eficacy 74lm/W 90°(90) Beam Angle Operating Temp. -20°C~+50°

