


Art Number
WL111105

Model
20W



Features

- Recessed spotlight with LED technique for various lighting tasks toll -free installation and maintenance
- Luminaire made from die cast thermal management with passive cooling
- Energy saving, no UV and thermal emissions
- High-quality aluminum reflector with latest specular optics for maximum luminous efficiency and glare free lighting
- High efficient LED UGR <22
- Life time 50000Hrs
- Other versions in Emergency and dimming are available

Product Specification

LED Chip	CREE LED
Power	20W
Input	100-240VAC Remote Driver
Lumen	1800lm(3K)/ 1890m(4K)/ 1985lm(5K)
CCT	3000K(30)/ 4000K(40)/ 5000K(50)
LED Type	COB LED
Power Factor	PF>0.9

Technical Data

IP Rating	IP20
Housing/ Front Cover	Die cast aluminum
Finishing	White(02)/ Black(04)
Reflector	Aluminum Reflector
Power Cable	H05RN-F 3x0.75 mm ² / L=0.5m
Mounting Sleeve	Stainless steel
Cutout	Ø100mm
Cooling	Passive

Photometric Data

CRI	80+
Luminous Efficacy	90lm/W
Beam Angle	15°(15)/ 30°(30)/ 45°(45)
Operating Temp.	-20°C-+45°

Order Code Example

Artnumber	Finish	Beam Angle	Color Temp
WL111108	WH(02)	15°(15)	3000K(30)
WL111108.02.15.30			