CRESCENT Ceiling Surfaced Downlight

Art Number

Mode

25W 220-240VAC





Features

CRESRNT series downlight adopts high lumen SMD LED as a light source Body made with extruded aluminum


Fire rated PC diffuser with even light output

IP54 waterproof structural design and ideal replacement for damp location Up to 70% energy saving compared to satandard CFL

Emergency function with smart IC control which swtiched automatically once the power is switched off.

Availabel in Four different size and wattage

Dimmable with 0-10V, Dali and Triac. other dimming will availabel upon the request



Product Specification


LED Chip SMD LED


Power 25W


Input 220-240VAC

Output 2575lm(2.7K)/2703lm(4K)/ 2839lm(5K)
CCT 2700K(27)/ 4000K(40)/ 5000K(50)

Driver Philips/ Tridonic







Technical Data

IP Rating IP54

Housing Extruded aluminum

Diffuser PC

Finishing White with sand(02)/Black with sand(04)

grey with sand(07)

Weight 1.30Kg
Package 10pcs/CTN
Power Factor PF>0.9

Photometric Data

 CRI
 90

 Luminous Eficacy
 103lm/W

 Beam Angle
 120°(120)

 Operating Temp.
 -20°C~+35°

Order Code Example			
Artnumber WL221022	Finish PAW <i>(02)</i> 	Beam Angle 60° <i>(60)</i>	Color Temp 2700K <i>(27</i>)
WL221022.02.60.27			

