

## Art Number

WL441044

## Model

120W 100-277VAC

WL441045

150W 100-277VAC



## Features

SKYLINE Series LED linear high bay light specially designed perfect lighting for aisles in warehouses.

It adopts high lumen LUMILED SMD 3030 as light source.

Modular design excellent performance and high lumen efficacy up to 130lm/W.

Luminaire body and heat sink construct with die cast aluminum with powder coated surface treatment.

Asymmetric optic lens adapts to narrow aisle well lighting between high shelves and racks.

Specially designed optics which gives not only contribute lighting lux level but also the best uniformity.

The rectangular luminaire design which can effectively reduce the light loss in aisles shelves.

Luminaire can provide intelligent lighting solutions with Dimming, sensors and emergency.

## Product Specification

LED Chip	Philips Lumi led 3030
Power	120W/ 150W
Input	100-277 VAC
Output	15600lm/ 19500lm
CCT	2700K(27)/ 3000K(30)/ 4000K(40)/ 6000K(60)
Driver	Sosen
Power Factor	>0.95
Module	Double

## Technical Data

IP Rating	IP65
IK Rate	IK10
Housing	Die cast aluminum
Heat sink	Die cast aluminum
Finishing	Black(04)
Power Cable	H05RN-F 3x0.75 mm <sup>2</sup> / L=0.5m (high voltage)
Mounting	Suspension chain, Bracket
Size	640x140x115mm

## Photometric Data

CRI	80
Luminous Efficacy	130lm/W
Beam Angle	40°(40)/ 90°(90)/ 30°x70°(A32)/125°x25°(A33)/ 150°x70°(A34)/ 120°(120)
Operating Temp.	-30°C-+50°

## Order Code Example

Artnumber	Finish	Beam Angle	Color Temp
WL441020	SLV(08)	60°(60)	3000K(30)
WL441020.08.60.30			

