


CEILING RECESSED IP54

Art Number	Model
WL111070	18W
WL111071	25W
WL111126	32W









Photometric Light Distribution


18W 3000K



25W 3000K



32W 3000K



Features

Broad series downlights adopts CITIZEN COB high efficiency with 114lm/W Body and trim made with die cast aluminum with powder coated

Traditional deep bright silver reflector (UGR<19) brings a good lighting effect for human beings.

Broad series square downlights offering beam angle 60° in different wattage such as 18W, 25W & 32W

Lifespan is up to 50,000 hrs

Other options in Emergency and dimmable are available Easy to install, use stainless steel spring, safe and durable

Product Specification

LED Chip CITIZEN LED
Power 18W/ 25W/ 32W

 Input
 220-240VAC Remote Driver

 Output
 1760lm/ 2420lm/ 3070lm

CCT 2700K(27)/ 3000K(30)/ 4000K(40)/ 5000K(50)

LED Type COB LED
Power Factor PF>0.9

Technical Data

IP Rating IP54

Housing/ Front Cover Die cast aluminum
Finishing White(02)/ Black(04)

Reflector Bright silver traditional deep reflector Power Cable H05RN-F $3x0.75 \text{ mm}^2/\text{L}=0.5\text{m}$

Mounting SleeveStainless steelCutout170x170mmWeight1.02KgPackage8pcs/CTN

Photometric Data

CRI 80

Luminous Eficacy 97lm/W

Beam Angle 60°(60)

Operating Temp. -20°C-+45°

Order Code	e Example				
Artnumber WL111066	Finish WH <i>(02)</i> 	Beam Angle 60°(60)	Color Temp 3000K(30)		
WL111066.02.60.30					

