# FLEXI STRIP \_\_\_\_

# 17.3W/m RGBW 60LED

Art Number WM991024 WM991025 WM991026 WM991047

Model IP20 IP65 IP68 IP67



### Features

Adopts High quality EPISTAR SMD5050 LED as a light source

- Available RGBW 4 in 1
- High brightness, low decay, stable quality
- Double layer copper flexible white PCB for good heat dissipation
- Good electricity and good conductivity
- Strong adhesive 3M double face tape for easy installation
- Every 10cm (6 LED) cutting mark, which helps you custom the length
- High operating temperature upto 50°C
- Available in IP20, IP65, IP67, IP68


#### Ingress Protection Structure




## Technical Data

Product Code	Power	Input	Lumen	CRI	LED/m	Beam Angle	Width	Length	IP Rate
WM991024	17.3W/m	24VDC	865lm/m	80+	60	120°	10mm	5m/Roll	IP20
WM991025	17.3W/m	24VDC	865lm/m	80+	60	120°	10mm	5m/Roll	IP65
WM991026	17.3W/m	24VDC	865lm/m	80+	60	120°	12mm	5m/Roll	IP68
WM991047	17.3W/m	24VDC	865lm/m	80+	60	120°	12mm	5m/Roll	IP67

#### 5050 300led White PCB



#### Suitable Profiles



WILMAR™ ARCHITECTURAL LIGHTING

We reserve the right to make technical changes without prior notice Electrical/Optical data are subjected to a tolerance of +/-10% www.wilmarintl.com