

Art Number	Model
WM991027	IP20
WM991028	IP65
WM991029	IP68
WM991048	IP67






Features

- Adopts High lumen EPISTAR SMD2835 LED as a light source
- Available CCT 2700K, 3000K, 4000K, 5000K, 6000K, RED, GREEN, BLUE
- High brightness, low decay, stable quality
- Double layer copper flexible white PCB for good heat dissipation
- Good electricity and good conductivity
- Strong adhesive 3M double face tape for easy installation
- Every 2.5cm (6 LED) cutting mark, which helps you custom the length
- High operating temperature upto 50°C
- Available in IP20, IP65, IP67, IP68




Ingress Protection Structure




Technical Data

Product Code	Power	Input	Lumen	CRI	LED/m	Beam Angle	Width	Length	IP Rate
WM991027	21W/m	24VDC	2000lm/m	80+	240	120°	10mm	5m/Roll	IP20
WM991028	21W/m	24VDC	2000lm/m	80+	240	120°	10mm	5m/Roll	IP65
WM991029	21W/m	24VDC	2000lm/m	80+	240	120°	12mm	5m/Roll	IP68
WM991048	21W/m	24VDC	2000lm/m	80+	240	120°	12mm	5m/Roll	IP67

2835 1200led White PCB



Suitable Profiles



Order Code Example

Artnumber Color Temp IP Rating
 WM991000 2700K(27) IP20(20)
 WM991000.27.20