

Art Number	Model
WM991003	IP20
WM991004	IP65
WM991005	IP68
WM991040	IP67



Features

- Adopts High lumen EPISTAR SMD2835 LED as a light source
- Available CCT 2700K, 3000K, 4000K, 5000K, 6000K, RED, GREEN, BLUE
- High brightness, low decay, stable quality
- Double layer copper flexible white PCB for good heat dissipation
- Good electricity and good conductivity
- Strong adhesive 3M double face tape for easy installation
- Every 20cm (6 LED) cutting mark, which helps you custom the length
- High operating temperature upto 50°C
- Available in IP20, IP65, IP67, IP68


Ingress Protection Structure



Technical Data

Product Code	Power	Input	Lumen	CRI	LED/m	Beam Angle	Width	Length	IP Rate
WM991003	6W/m	24VDC	510lm/m	80+	30	120°	8mm	5m/Roll	IP20
WM991004	6W/m	24VDC	510lm/m	80+	30	120°	8mm	5m/Roll	IP65
WM991005	6W/m	24VDC	510lm/m	80+	30	120°	10mm	5m/Roll	IP68
WM991040	6W/m	24VDC	510lm/m	80+	30	120°	10mm	5m/Roll	IP67

2835 150led White PCB



Suitable Profiles

