


Art Number	Model
WL921019	12W 100-240VAC H800
WL921022	25W 100-240VAC H1000



Features

URIAH series bollard light adopts CREE led as a light source.
 Made of robust design die-cast aluminium cover, extruded aluminium pole.
 The surface anti ageing spray process
 Reflector made of pure anodized aluminium and clear tempered glass light transmission with high strength silicon rubber seal.
 The luminaire provides diffused light distribution which is suitable for the anti-glare illumination of the ground surface.
 It is giving the visually treat the illuminating in the garden and public areas.
 IP65 fixture is suitable in outdoor, public and landscape lighting applications.

Product Specification

LED Chip	CREE LED
Power	12W/ 25W
Input	100-240VAC
Output	980lm/ 1850lm
CCT	2700K(27)/ 3000K(30)/ 4000K(40)/ 6000K(60)
LED Type	SMD LED

Technical Data

Power Factor	>0.9
IP Rating	IP65
IK Rating	IK08
Housing	Die cast aluminum, extruded aluminum pole
Finishing	Black(04), Grey(06)
Diffuser	PMMA
Power Cable	H05RN-F 3x0.75 mm ² / L=0.5m (high voltage)
Mounting	Mounting plate with luminaire inside two screw

Photometric Data

CRI	80
Luminous Efficacy	74-81lm/W
Beam Angle	Radial 2 Side (R2)
Operating Temp.	-35°C~+55°

Order Code Example

Artnumber	Finish	Beam Angle	Color Temp
WL921023	BL(04)	Diffused(D)	3000K(30)
WL921023.04.D.30			