


Art Number	Model
WL921020	16W 100-240VAC H800
WL921030	16W 100-240VAC H300



## Features

LYLE bollard light adopts CREE led as a light source.  
 Made of robust design die-cast aluminium alloy with cost-effective and durable LED technology.  
 Good corrosion resistance fluorocarbon paint processing coating.  
 Reflector made of pure anodized aluminium and clear tempered glass light transmission with high strength silicon rubber seal.  
 The luminaire provides diffused light distribution which is suitable for the anti-glare illumination of the ground surface.  
 It is giving the visually treat the illuminating in the gardens, driveways and footpath.  
 IP65 fixture is suitable in outdoor, public and landscape lighting applications.

## Product Specification

LED Chip	CREE LED
Power	16W
Input	100-240VAC
Output	1600lm
CCT	2700K(27)/ 3000K(30)/ 4000K(40)/ 6000K(60)
LED Type	High Power

## Technical Data

Power Factor	>0.9
IP Rating	IP65
IK Rating	IK08
Housing	Die cast aluminum alloy
Finishing	Black(04), Grey(06)
Light Window	Clear tempered glass
Reflector	Anodized aluminum
Power Cable	H05RN-F 3x0.75 mm <sup>2</sup> / L=0.5m (high voltage)
Mounting	Mounting plate with luminaire inside two screw

## Photometric Data

CRI	80
Luminous Efficacy	100lm/W
Beam Angle	Diffused (D)
Operating Temp.	-35°C~+55°

### Order Code Example

Artnumber	Finish	Beam Angle	Color Temp
WL921025	BL(04)	Diffused(D)	3000K(30)
WL921023.04.D.30			